



One Source for Precision Fibrous Parts

EL1-KS POLISHING MATERIAL

<u>DESCRIPTION:</u>	Durable Premium Polishing Pad
<u>FOR USE ON:</u>	Most Semiconductor, Compound Semi, Optic/Electro-Optic & Sapphire Applications
<u>DUROMETER:</u>	C Scale 58
<u>COMPRESSION:</u>	2% (1/2 lb. force displacement)
<u>DENSITY:</u>	.53 g/cm ³ (25 lb.)
<u>THICKNESS:</u>	0.050"
<u>DIAMETER:</u>	Up To 60" Sheets or Pads
<u>BACKINGS:</u>	Easy Apply/Remove PSA Is Standard. High Temperature PSA and Magnetic Backing Are Available Upon Request
<u>CAN REPLACE:</u>	Suba Series Pads
<u>PERFORMANCE:</u>	Performs well with colloidal silica, cerium oxide, alumina and diamond compound slurries. Can be used as a single step pad with the proper slurry formulations and machine parameter settings on many materials.

SPARTAN FELT COMPANY
151 Felt Drive, Roebuck, SC 29376
TEL: 864-576-7919
www.spartanfelt.com
e-mail: jwerty@spartanfelt.com

MANUFACTURERS OF PRECISION FELT PRODUCTS

